# NSN 5320-01-392-2526

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-392-2526



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.865 inches and 1.885 inches

# Head Style:

Err-090

#### Head Height:

Between 0.102 inches and 0.112 inches

# Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3110 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

Between 0.475 inches and 0.505 inches

# Grip Length:

Between 1.370 inches and 1.380 inches

# Min. Tensile Strength (psi):

210000 pounds per square inch

# Thread Size:

0.3125 inches

# Shear Strength:

125000 single pounds per square inch

#### Material:

Nickel alloy 718

# **Material Specification:**

Ams5662 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

258, cagec 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-392-2526

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

