NSN 5320-01-392-3381

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-3381

Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 1.613 inches and 1.633 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.2207 inches and 0.2242 inches
Shank Diameter:
Between 0.4990 inches and 0.4995 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 1.0068 inches and 1.0139 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.933 inches and 0.943 inches
Min. Tensile Strength (psi):
25500 pounds per square inch
Thread Size:
0.500 inches
Shear Strength:
37300 double pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Grit blast top of head, with color light blue on thread end.
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
73197-hlt453 manufacturers standard
Shelf Life:
N/a

NSN 5320-01-392-3381

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0