## NSN 5320-01-392-3390

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-3390 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 0.753 inches and 0.773 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.1890 inches and 0.1895 inches **Grip Length:** Between 0.433 inches and 0.443 inches Min. Tensile Strength (psi): 210000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 130.0 degrees **Special Features:** Light orange dye on the chamfer. Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

-- Demilitarization:

## NSN 5320-01-392-3390

Pin-rivet - Page 2 of 2



Fiig:

A528u0