NSN 5320-01-392-3391

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-3391 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.073 inches and 1.093 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style: Head Major Diameter:** Between 0.5026 inches and 0.5111 inches **Grip Length:** Between 0.683 inches and 0.693 inches Min. Tensile Strength (psi): 210000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 130.0 degrees **Special Features:** Light orange dye on the chamfer. Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-392-3391

Pin-rivet - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A528u0