NSN 5320-01-392-3411

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-3411
Identification Code Color:
Gray
Fastener Length:
0.892 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.2575 inches and 0.2595 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
Between 0.463 inches and 0.507 inches
Expansion Device:
Threaded stem and expander
Lubrication:
Cetyl alcohol or carbo wax or paraffin wax
Grip Length:
Between 0.150 inches and 0.200 inches
Features Provided:
Drive nut
Min. Tensile Strength (psi):
2100 pounds per square inch
Shear Strength:
7900 double pounds per square inch
Countersink Angle:
Between 129.0 degrees and 131.0 degrees
Special Features:
Powder blast top of head.
Material:
Titanium alloy uns r56400 body
Material Specification:
Ams5731 assn standard single material response stem or ams5732 assn standard single material response stem or ams5737 assn standard
single material response stem
Surface Treatment:
Passivate stem
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response stem
Specification Data:
76823-03a146 manufacturers standard
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5320-01-392-3411

Blind Rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A040a0