NSN 5320-01-392-3411

Blind Rivet - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5320-01-392-3411 |
|---|
| Identification Code Color: |
| Gray |
| Fastener Length: |
| 0.892 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.2575 inches and 0.2595 inches |
| Shank Style: |
| Threaded self-plugging shank w/sleeve |
| Head Major Diameter: |
| Between 0.463 inches and 0.507 inches |
| Expansion Device: |
| Threaded stem and expander |
| Lubrication: |
| Cetyl alcohol or carbo wax or paraffin wax |
| Grip Length: |
| Between 0.150 inches and 0.200 inches |
| Features Provided: |
| Drive nut |
| Min. Tensile Strength (psi): |
| 2100 pounds per square inch |
| Shear Strength: |
| 7900 double pounds per square inch |
| Countersink Angle: |
| Between 129.0 degrees and 131.0 degrees |
| Special Features: |
| Powder blast top of head. |
| Material: |
| Titanium alloy uns r56400 body |
| Material Specification: |
| Ams5731 assn standard single material response stem or ams5732 assn standard single material response stem or ams5737 assn standard |
| single material response stem |
| Surface Treatment: |
| Passivate stem |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response stem |
| Specification Data: |
| 76823-03a146 manufacturers standard |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 5320-01-392-3411

Blind Rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A040a0