

View Online at <https://aerobasegroup.com/nsn/5320-01-392-3412>

**Fastener Length:**

1.050 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.2255 inches and 0.2275 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.373 inches and 0.416 inches

**Expansion Device:**

Threaded stem and knob stem-type k

**Lubrication:**

Cetyl alcohol or carbo wax or paraffin wax

**Grip Length:**

Between 0.350 inches and 0.400 inches

**Min. Tensile Strength (psi):**

1600 pounds per square inch

**Shear Strength:**

5600 double pounds per square inch

**Countersink Angle:**

Between 129.0 degrees and 131.0 degrees

**Special Features:**

Powder blast top of head. Drive nut, corrosion resistant coating, color grey.

**Material:**

Titanium alloy uns r56400 body

**Material Specification:**

Ams5731 assn standard single material response stem or ams5732 assn standard single material response stem or ams5737 assn standard single material response stem

**Surface Treatment:**

Passivate stem

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response stem

**Specification Data:**

76823-03a146 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0