

View Online at <https://aerobasegroup.com/nsn/5320-01-392-3414>

Identification Code Color:

Gray

Fastener Length:

0.942 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2575 inches and 0.2595 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.463 inches and 0.507 inches

Expansion Device:

Threaded stem and expander

Lubrication:

Cetyl alcohol or carbo wax or paraffin wax

Grip Length:

Between 0.200 inches and 0.250 inches

Features Provided:

Drive nut

Min. Tensile Strength (psi):

2100 pounds per square inch

Minimum Yield Strength:

2100 pounds per square inch

Shear Strength:

7900 double pounds per square inch

Countersink Angle:

Between 129.0 degrees and 131.0 degrees

Special Features:

Powder blast top of head.

Material:

Titanium alloy uns r56400 body

Material Specification:

Ams5731 assn standard single material response stem or ams5732 assn standard single material response stem or ams5737 assn standard single material response stem

Surface Treatment:

Passivate stem

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response stem

Specification Data:

76823-03a146 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0