NSN 5320-01-392-3414

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-3414 **Identification Code Color:** Gray Fastener Length: 0.942 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.2575 inches and 0.2595 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Head Major Diameter:** Between 0.463 inches and 0.507 inches **Expansion Device:** Threaded stem and expander Lubrication: Cetyl alcohol or carbo wax or paraffin wax **Grip Length:** Between 0.200 inches and 0.250 inches **Features Provided:** Drive nut Min. Tensile Strength (psi): 2100 pounds per square inch Minimum Yield Strength: 2100 pounds per square inch **Shear Strength:** 7900 double pounds per square inch **Countersink Angle:** Between 129.0 degrees and 131.0 degrees **Special Features:** Powder blast top of head. Material: Titanium alloy uns r56400 body **Material Specification:** Ams5731 assn standard single material response stem or ams5732 assn standard single material response stem or ams5737 assn standard single material response stem **Surface Treatment:** Passivate stem **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response stem **Specification Data:**

Shelf Life:

76823-03a146 manufacturers standard

N/a

NSN 5320-01-392-3414

Blind Rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A040a0