

View Online at <https://aerobasegroup.com/nsn/5320-01-392-4248>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.3125 inches

Head Style:

Err-090

Head Height:

Between 0.102 inches and 0.112 inches

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3110 inches and 0.3120 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.475 inches and 0.505 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.812 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.3040 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Furnished w/ undersized thd dia; color light blue on thd end

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-kote 1, caged 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0