## NSN 5320-01-392-5045

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-5045 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 2.832 inches **Head Style:** Err-090 **Head Height:** Between 0.200 inches and 0.210 inches Width Between Flats: Between 0.2520 inches and 0.2555 inches **Shank Diameter:** Between 0.5610 inches and 0.5615 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.842 inches and 0.877 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 2.062 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.5525 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Furnished w/ undersized thd dia; grit blast top of head, color light blue on thd end. Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-392-5045

Pin-rivet - Page 2 of 2



Fiig:

A528u0