## NSN 5320-01-392-5118

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-392-5118



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.877 inches and 0.897 inches

#### Head Style:

Err-090

## Width Between Flats:

Between 0.0791 inches and 0.0806 inches

## Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

#### Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

#### Lubrication:

Solid film and cetyl alcohol

#### Grip Length:

Between 0.557 inches and 0.567 inches

## Min. Tensile Strength (psi):

2600 pounds per square inch

## Thread Size:

0.190 inches

#### Shear Strength:

7060 double pounds per square inch

#### **Countersink Angle:**

100.0 degrees

## **Special Features:**

White paint color number 37875 per fed-std-595, on top of head.

#### Material:

Steel comp xm-13

#### Material Specification:

Ams5629 assn standard single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

#### **Specification Data:**

76301-st3-758 manufacturers standard

# NSN 5320-01-392-5118

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

