NSN 5320-01-392-5118

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-5118 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.877 inches and 0.897 inches **Head Style:** Err-090 Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style: Head Major Diameter:** Between 0.2966 inches and 0.3016 inches Lubrication: Solid film and cetyl alcohol **Grip Length:** Between 0.557 inches and 0.567 inches Min. Tensile Strength (psi): 2600 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 7060 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** White paint color number 37875 per fed-std-595, on top of head. Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unjf

Specification Data:

76301-st3-758 manufacturers standard

NSN 5320-01-392-5118

Pin-rivet - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0