

View Online at <https://aerobasegroup.com/nsn/5320-01-392-5126>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.927 inches and 0.947 inches

Head Style:

Err-090

Head Height:

Between 0.055 inches and 0.065 inches

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Shank Diameter:

Between 0.1630 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.306 inches and 0.322 inches

Lubrication:

Solid film and cetyl alcohol

Grip Length:

Between 0.620 inches and 0.630 inches

Min. Tensile Strength (psi):

2940 pounds per square inch

Thread Size:

0.164 inches

Shear Strength:

5280 double pounds per square inch

Special Features:

Color white on top of head.

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

76301-st3-761 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0