

View Online at <https://aerobasegroup.com/nsn/5320-01-392-5135>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.864 inches and 0.884 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.055 inches and 0.065 inches

**Width Between Flats:**

Between 0.0791 inches and 0.0801 inches

**Shank Diameter:**

Between 0.1630 inches and 0.1635 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.306 inches and 0.322 inches

**End Application:**

W/s: f/a-18e/f hornet aircraft; aircraft, hornet f/a-18

**Grip Length:**

Between 0.557 inches and 0.567 inches

**Min. Tensile Strength (psi):**

2940 pounds per square inch

**Thread Size:**

0.164 inches

**Special Features:**

Color white on top of head.

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Specification Data:**

73197-hlt52 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0