# NSN 5320-01-392-6405

Pin-rivet - Page 1 of 2



AeroBase Group

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

1.325 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.064 inches and 0.074 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.357 inches and 0.377 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

1.000 inches

# Min. Tensile Strength (psi):

160000 pounds per square inch

#### Thread Size:

0.1825 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Special Features:**

Furnisned w/ undersized thd dia; color light blue on thd end

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Surface Treatment:

Aluminum alloy

# Surface Treatment Specification:

Hi-kote no. 1, cagec 73197 mfr ref single treatment response

# Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5320-01-392-6405

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

