

View Online at <https://aerobasegroup.com/nsn/5320-01-392-7388>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.938 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.102 inches and 0.112 inches

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3110 inches and 0.3120 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.475 inches and 0.505 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.438 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.304 inches

**Shear Strength:**

95000 single pounds per square inch

**Special Features:**

Furnished w/ undersized thd dia; color light blue on thd end.

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Surface Treatment:**

Aluminum alloy

**Surface Treatment Specification:**

Hi-kote no. 1, caged 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0