# NSN 5320-01-392-7390

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-7390

**Thread Class:** 

3a

**Thread Direction:** 

Right-hand

## Fastener Length:

1.5606 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.130 inches and 0.140 inches

#### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3740 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.565 inches and 0.600 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

1.0156 inches

# Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.366 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Special Features:**

Furnished w/ undersized thd dia; grit blast top of head, color light blue on thd dia

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Thread Series Designator:

Unjf

# Shelf Life:

N/a

### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-392-7390

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

