NSN 5320-01-392-7393

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-7393 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.000 inches **Head Style:** Err-090 **Head Height:** Between 0.102 inches and 0.112 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.500 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.304 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Furnished w/ undersized thd dia; color light blue on thd end.D Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum alloy **Surface Treatment Specification:** Hi-kote no. 1, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5320-01-392-7393

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0