Pin-rivet - Page 1 of 2





**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

0.750 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.055 inches and 0.065 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0801 inches

#### Shank Diameter:

Between 0.1625 inches and 0.1635 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.306 inches and 0.322 inches

### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

0.438 inches

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### Thread Size:

0.1582 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Special Features:**

Furnished w/ undersized thd dia; color light blue on thd end.

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum alloy

## Surface Treatment Specification:

Hi-kote no. 1, cagec 73197 mfr ref single treatment response

## Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5320-01-392-8113

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

