## NSN 5320-01-392-8541

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-8541 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Green **Fastener Length:** Between 0.877 inches and 0.897 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.382 inches and 0.391 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.557 inches and 0.567 inches Min. Tensile Strength (psi): 2000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 130.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ms 4967 assn standard single material response **Surface Treatment:** Phosphate **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-392-8541

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0