NSN 5320-01-393-0833

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-393-0833

Between 0.302 inches and 0.322 inches Head Style: Universal Head Height: Between 0.054 inches and 0.064 inches Shank Diameter: Between 0.124 inches and 0.128 inches Shank Style: Straight w/radius chamfered tip
Universal Head Height: Between 0.054 inches and 0.064 inches Shank Diameter: Between 0.124 inches and 0.128 inches Shank Style:
Head Height: Between 0.054 inches and 0.064 inches Shank Diameter: Between 0.124 inches and 0.128 inches Shank Style:
Between 0.054 inches and 0.064 inches Shank Diameter: Between 0.124 inches and 0.128 inches Shank Style:
Shank Diameter: Between 0.124 inches and 0.128 inches Shank Style:
Between 0.124 inches and 0.128 inches Shank Style:
Shank Style:
Straight w/radius chamfered tip
9
Head Major Diameter:
Between 0.213 inches and 0.262 inches
Heat Treatment:
H-32 strain hardened
Material:
Aluminum alloy 5056
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type ii, class 1, clear military specification single treatment response
Specification Data:
96906-ms20470 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-a-8625 spec.