

View Online at <https://aerobasegroup.com/nsn/5320-01-393-0850>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.645 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.080 inches and 0.090 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2485 inches and 0.2495 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.415 inches and 0.440 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

Aircraft, b-2 bomber (atb)

**Grip Length:**

1.250 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.2425 inches

**Shear Strength:**

95000 single pounds per square inch

**Special Features:**

Furnished w/ undersized thd dia; color light blue on thd end.

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Surface Treatment:**

Aluminum alloy

**Surface Treatment Specification:**

Hi-kote n0. 1, cagc 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0