NSN 5320-01-393-0850

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-393-0850

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
1.645 inches
Head Style:
Err-090
Head Height:
Between 0.080 inches and 0.090 inches
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2485 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.415 inches and 0.440 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
End Application:
Aircraft, b-2 bomber (atb)
Grip Length:
1.250 inches
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.2425 inches
Shear Strength:
95000 single pounds per square inch
Special Features:
Furnished w/ undersized thd dia; color light blue on thd end.
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Aluminum alloy
Surface Treatment Specification:
Hi-kote n0. 1, cagec 73197 mfr ref single treatment response
Thread Series Designator:
Unjf

NSN 5320-01-393-0850

Pin-rivet - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0