NSN 5320-01-393-1322

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Fastener Length:

Between 1.190 inches and 1.210 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-393-1322

Head Style:						
Err-090						
Head Height:						
Between 0.045 inches and 0.055 inches						
Width Between Flats:						
Between 0.0791 inches and 0.0806 inches						
Shank Diameter:						
Between 0.1890 inches and 0.1895 inches						
Shank Style:						
Head Major Diameter:						
Between 0.295 inches and 0.315 inches						
Lubrication:						
Cetyl alcohol, specification 305, hi-shear corp						
Grip Length:						
Between 0.870 inches and 0.880 inches						
Min. Tensile Strength (psi):						
3000 pounds per square inch						
Thread Size:						
0.190 inches						
Shear Strength:						
7060 double pounds per square inch						
Special Features:						
White paint on top of head.						
Material:						
Steel comp xm-13						
Material Specification:						
Ams5629 assn standard single material response						
Surface Treatment:						
Passivate						
Surface Treatment Specification:						
Qq-p-35 federal specification single treatment response						
Thread Series Designator:						
Unjf						
Specification Data:						
73197-hl644 manufacturers standard						

NSN 5320-01-393-1322

Pin-rivet - Page 2 of 2



_				• •	
•	hΔ	1+		.ife	•
J			_	.116	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0