NSN 5320-01-393-5734

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-393-5734 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Black **Fastener Length:** Between 4.947 inches and 4.967 inches **Head Style:** Straight pan **Head Height:** Between 0.077 inches and 0.090 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.415 inches and 0.440 inches **Tip Diameter:** Between 0.2410 inches and 0.2440 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 4.557 inches and 4.567 inches Min. Tensile Strength (psi): 6320 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 9300 single pounds per square inch Material: Iron alloy 651 **Material Specification:** Ams 5721 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:
No

NSN 5320-01-393-5734

Pin-rivet - Page 2 of 2



Fiig:

A528u0