NSN 5320-01-395-7677

Solid Rivet - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5320-01-395-7677 |
|--|
| Fastener Length: |
| Between 0.3025 inches and 0.3225 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.093 inches and 0.097 inches |
| Shank Style: |
| Straight w/radius chamfered tip |
| Head Major Diameter: |
| Between 0.175 inches and 0.183 inches |
| Countersink Angle: |
| Between 99.5 degrees and 100.5 degrees |
| Heat Treatment: |
| T-4 solution heat treated |
| Material: |
| Aluminum alloy 2117 |
| Material Specification: |
| Qq-a-430 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type ii, class 1, clear military specification single treatment response |
| Specification Data: |
| 96906-ms20426 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |

Mil-std (military Standard):

Mil-a-8625 spec.