## NSN 5320-01-396-2936

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-396-2936 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 1.077 inches and 1.097 inches **Head Style:** Straight pan **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.122 inches and 0.142 inches **Shank Diameter:** Between 0.2696 inches and 0.2701 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and solid film **Grip Length:** Between 0.562 inches and 0.572 inches Min. Tensile Strength (psi): 4300 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 10800 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response **Surface Treatment:** Anodize **Thread Series Designator:** 

Unjf
Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No

## NSN 5320-01-396-2936

Pin-rivet - Page 2 of 2



Fiig:

A528u0