NSN 5320-01-397-0328

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-397-0328

view Offinie at https://aerobasegroup.com/hsh/3525-01-537-0520
Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Yellow
Fastener Length:
Between 1.175 inches and 1.195 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2802 inches and 0.2807 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.5018 inches and 0.5066 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.745 inches and 0.755 inches
Min. Tensile Strength (psi):
7750 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
12260 double pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Top surface of head shall be powder blasted, with color yellow on thread end.
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response

Unjf

Thread Series Designator:

NSN 5320-01-397-0328

Pin-rivet - Page 2 of 2



\r		•	C 2 t	ınn	11212	Į
OL.	, .		Cal	UII	Data	,

76823-03a063 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0