

View Online at <https://aerobasegroup.com/nsn/5320-01-397-0328>

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Yellow

Fastener Length:

Between 1.175 inches and 1.195 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2802 inches and 0.2807 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.5018 inches and 0.5066 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.745 inches and 0.755 inches

Min. Tensile Strength (psi):

7750 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

12260 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Top surface of head shall be powder blasted, with color yellow on thread end.

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

76823-03a063 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0