## NSN 5320-01-398-1305

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-398-1305 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.785 inches and 0.825 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2016 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.263 inches and 0.305 inches **Grip Length:** Between 0.439 inches and 0.500 inches **Thread Size:** 0.190 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Oversize and restricted for use in repair work only. Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams2416 assn standard single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas4452 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-398-1305

Pin-rivet - Page 2 of 2



Fiig:

A528u0