## NSN 5320-01-398-1768

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-398-1768

**Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Blue **Fastener Length:** Between 0.678 inches and 0.698 inches **Head Style:** Err-090 **Head Height:** Between 0.102 inches and 0.112 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.183 inches and 0.193 inches Min. Tensile Strength (psi): 9200 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 14600 double pounds per square inch **Special Features:** Color light blue on thread end. Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** 

Unjf

**Specification Data:** 

73197-hlt452 manufacturers standard

## NSN 5320-01-398-1768

Pin-rivet - Page 2 of 2



_						
C	he	14		iŧ	0	•
J			_		ㄷ	-

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0