NSN 5320-01-398-2319

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-398-2319

| View Online at https://aerobasegroup.com/nsn/5320-01-398-2319 |
|------------------------------------------------------------------------------|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Identification Code Color: |
| Yellow |
| Fastener Length: |
| Between 0.850 inches and 0.870 inches |
| Head Style: |
| Err-090 |
| Head Height: |
| Between 0.064 inches and 0.074 inches |
| Width Between Flats: |
| Between 0.0791 inches and 0.0806 inches |
| Shank Diameter: |
| Between 0.2016 inches and 0.2026 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.357 inches and 0.377 inches |
| Lubrication: |
| Solid film and cetyl alcohol |
| Grip Length: |
| Between 0.495 inches and 0.505 inches |
| Min. Tensile Strength (psi): |
| 4350 pounds per square inch |
| Thread Size: |
| 0.190 inches |
| Shear Strength: |
| 7060 double pounds per square inch |
| Special Features: |
| Caution, restricted usage, for repair work only. Color yellow on thread end. |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams5662 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 76823-03a064 manufacturers standard |
| Shelf Life: |
| A1/ |

N/a

NSN 5320-01-398-2319

Pin-rivet - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A528u0