NSN 5320-01-398-2324

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-398-2324

View Offiline at https://derobasegroup.com/nsn/3520-01-550-2524
Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Yellow
Fastener Length:
Between 0.925 inches and 0.945 inches
Head Style:
Err-090
Head Height:
Between 0.080 inches and 0.090 inches
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2646 inches and 0.2651 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.415 inches and 0.440 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.495 inches and 0.505 inches
Min. Tensile Strength (psi):
7750 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
12260 double pounds per square inch
Special Features:
Powder blast top of head, with color yellow on thread end. Caution, oversize, restricted usage, for repair work only.
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
76823-03a064 manufacturers standard
Shelf Life:

N/a

NSN 5320-01-398-2324

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0