## NSN 5320-01-398-3613

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-398-3613 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Yellow **Fastener Length:** Between 1.410 inches and 1.430 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.127 inches and 0.129 inches **Shank Diameter:** Between 0.326 inches and 0.327 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.628 inches and 0.633 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.870 inches and 0.880 inches Min. Tensile Strength (psi): 12300 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 19160 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-01-398-3613

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0