NSN 5320-01-398-3617

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-398-3617 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Black **Fastener Length:** Between 0.440 inches and 0.460 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3765 inches and 0.3813 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.120 inches and 0.130 inches Min. Tensile Strength (psi): 2750 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 5380 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Powder blast top of head, with color light blue on thread end.

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

76823-03a073 manufacturers standard

Shelf Life:

N/a

NSN 5320-01-398-3617

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0