

View Online at <https://aerobasegroup.com/nsn/5320-01-398-3622>

Fastener Length:

0.953 inches

Head Style:

Hexagon

Head Height:

0.135 inches

Shank Diameter:

Between 0.2580 inches and 0.2600 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded stem and expander

Lubrication:

Cetyl alcohol or carbo wax or paraffin wax

Grip Length:

Between 0.345 inches and 0.406 inches

Width Across Flats:

Between 0.367 inches and 0.375 inches

Features Provided:

Drive nut and self-locking

Min. Tensile Strength (psi):

2100 pounds per square inch

Shear Strength:

7900 double pounds per square inch

Special Features:

Corrosion resisting coating, color gray or black on drive nut.

Material:

Titanium alloy uns r56400 stem

Material Specification:

Ams5639 assn standard single material response sleeve or ams5641 assn standard single material response sleeve or ams5731 assn standard single material response sleeve or ams5732 assn standard single material response sleeve or ams5737 assn standard single material response sleeve

Surface Treatment:

Aluminum sleeve

Surface Treatment Specification:

Nas4006 assn standard single treatment response nut

Specification Data:

76823-03a054 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0