

View Online at <https://aerobasegroup.com/nsn/5320-01-398-3622>

**Fastener Length:**

0.953 inches

**Head Style:**

Hexagon

**Head Height:**

0.135 inches

**Shank Diameter:**

Between 0.2580 inches and 0.2600 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Threaded stem and expander

**Lubrication:**

Cetyl alcohol or carbo wax or paraffin wax

**Grip Length:**

Between 0.345 inches and 0.406 inches

**Width Across Flats:**

Between 0.367 inches and 0.375 inches

**Features Provided:**

Drive nut and self-locking

**Min. Tensile Strength (psi):**

2100 pounds per square inch

**Shear Strength:**

7900 double pounds per square inch

**Special Features:**

Corrosion resisting coating, color gray or black on drive nut.

**Material:**

Titanium alloy uns r56400 stem

**Material Specification:**

Ams5639 assn standard single material response sleeve or ams5641 assn standard single material response sleeve or ams5731 assn standard single material response sleeve or ams5732 assn standard single material response sleeve or ams5737 assn standard single material response sleeve

**Surface Treatment:**

Aluminum sleeve

**Surface Treatment Specification:**

Nas4006 assn standard single treatment response nut

**Specification Data:**

76823-03a054 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0