NSN 5320-01-398-3623

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-398-3623 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Yellow **Fastener Length:** Between 1.550 inches and 1.570 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.094 inches and 0.096 inches **Shank Diameter:** Between 0.264 inches and 0.265 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.501 inches and 0.506 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.120 inches and 1.130 inches Min. Tensile Strength (psi): 7750 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 12260 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Nickel alloy k-500 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-398-3623

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0