## NSN 5320-01-398-4075

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

**Thread Direction:** 

**Identification Code Color:** 

За

Blue



View Online at https://aerobasegroup.com/nsn/5320-01-398-4075

Fastener Length:						
Between 0.690 inches and 0.710 inches						
Head Style:						
Err-090						
Head Height:						
Between 0.064 inches and 0.074 inches						
Width Between Flats:						
Between 0.0791 inches and 0.0806 inches						
Shank Diameter:						
Between 0.1890 inches and 0.1895 inches						
Shank Style:						
•						
Head Major Diameter:						
Between 0.357 inches and 0.377 inches						
Lubrication:						
Cetyl alcohol, specification 305, hi-shear corp						
Grip Length:						
Between 0.370 inches and 0.380 inches						
Min. Tensile Strength (psi):						
4350 pounds per square inch						
Thread Size:						
0.190 inches						
Shear Strength:						
7060 double pounds per square inch						
Material:						
Nickel alloy 718						
Material Specification:						
Ams5662 assn standard single material response						
Surface Treatment:						
Passivate						
Surface Treatment Specification:						
Spec 258, 73197 mfr ref single treatment response						
Thread Series Designator:						
Unjf						
Specification Data:						
26512-gb511gc manufacturers standard						

## NSN 5320-01-398-4075

Pin-rivet - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0