
NSN 5320-01-398-4082

Pin-rivet - Page 1 of 2

Thread Class:

3a



AeroBase Group

Thread Direction: Right-hand Identification Code Color: Blue **Fastener Length:** Between 0.753 inches and 0.773 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches Shank Diameter: Between 0.1890 inches and 0.1895 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.357 inches and 0.377 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.433 inches and 0.443 inches Min. Tensile Strength (psi): 4350 pounds per square inch **Thread Size:** 0.190 inches Shear Strength: 7060 double pounds per square inch Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Spec 258, 73197 mfr ref single treatment response **Thread Series Designator:** Unjf **Specification Data:** 26512-gb511gc manufacturers standard

NSN 5320-01-398-4082

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

