

View Online at <https://aerobasegroup.com/nsn/5320-01-398-9117>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.375 inches and 1.395 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.190 inches and 0.193 inches

**Shank Diameter:**

Between 0.436 inches and 0.437 inches

**Shank Style:**

**Head Major Diameter:**

Between 0.881 inches and 0.999 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

B-1b

**Grip Length:**

Between 0.760 inches and 0.780 inches

**Thread Qty Per Inch (tpi):**

20

**Thread Size:**

0.437 inches

**Shear Strength:**

125000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Pin, hi lock

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Hi-shear spec258, cagec73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0