

View Online at <https://aerobasegroup.com/nsn/5320-01-399-2057>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.597 inches and 1.617 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3271 inches and 0.3276 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.6287 inches and 0.6335 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.057 inches and 1.067 inches

Min. Tensile Strength (psi):

9200 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

16000 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Grit blast top of head, with color white on thread end, 1/64" oversize, for repair work only.

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

73197-hlt437 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0