NSN 5320-01-399-2060

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-399-2060 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.847 inches and 1.867 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3271 inches and 0.3276 inches **Shank Style: Head Major Diameter:** Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.307 inches and 1.317 inches Min. Tensile Strength (psi): 9200 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 16000 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Grit blast top of head, with color white on thread end, 1/64" oversize, for repair work only. Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 73197-hlt437 manufacturers standard Shelf Life: N/a **Unit Of Measure:**

--

NSN 5320-01-399-2060

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0