

View Online at <https://aerobasegroup.com/nsn/5320-01-399-2061>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.205 inches and 1.225 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.3896 inches and 0.3901 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.7556 inches and 0.7604 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.620 inches and 0.630 inches

Min. Tensile Strength (psi):

14000 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

22700 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Grit blast top of head, with color white on thread end, 1/64" oversize, (for repair work only)

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

73197-hlt437 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0