

View Online at <https://aerobasegroup.com/nsn/5320-01-399-2088>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.315 inches and 2.335 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.2520 inches and 0.2555 inches

Shank Diameter:

Between 0.5766 inches and 0.5771 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 1.1337 inches and 1.1408 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.495 inches and 1.505 inches

Min. Tensile Strength (psi):

32400 pounds per square inch

Thread Size:

0.562 inches

Shear Strength:

49700 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Grit blast top of head, with color white on thread end, 1/64" oversize, (for repair work only)

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

73197-hlt437 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0