# NSN 5320-01-399-2095

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-01-399-2095



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 1.518 inches and 1.538 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.130 inches and 0.140 inches

#### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3896 inches and 0.3901 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.565 inches and 0.600 inches

### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

### Grip Length:

Between 0.933 inches and 0.943 inches

### Min. Tensile Strength (psi):

160000 pounds per square inch

### Thread Size:

0.375 inches

#### **Special Features:**

Power blast parts and white dye should be on parts

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response

## **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A528u0