# NSN 5320-01-399-3166

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-01-399-3166



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 0.737 inches and 0.757 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

#### Width Between Flats:

Between 0.094 inches and 0.096 inches

#### Shank Diameter:

Between 0.2646 inches and 0.2651 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.415 inches and 0.440 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

Between 0.307 inches and 0.317 inches

## Min. Tensile Strength (psi):

16000 pounds per square inch

#### Thread Size:

0.250 inches

#### **Special Features:**

Power blast and color with white dye

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response

#### **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A528u0