## NSN 5320-01-399-3832



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-399-3832 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.425 inches and 1.445 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2646 inches and 0.2651 inches **Shank Style: Head Major Diameter:** Between 0.5018 inches and 0.5066 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.995 inches and 1.005 inches Min. Tensile Strength (psi): 5820 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 10490 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Grit blast top of head, with color white on thread end, 1/64" oversize, for repair work only. Material: Titanium alloy uns r56400 **Material Specification:** 

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Thread Series Designator:** 

Unjf

**Specification Data:** 

73197-hlt437 manufacturers standard

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-01-399-3832

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0