NSN 5320-01-399-4374

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-399-4374 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.565 inches and 0.585 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2021 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** B-1b acft **Grip Length:** Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2500 pounds per square inch **Thread Size:** 1.000 inches **Shear Strength:** 6130 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-399-4374

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0